



Cable & Accessories | Flexible Cables

Cable 3182Y 2C Flex PVC 0.75mm Whi(100m)

Cable 3182Y 2C Flex PVC
0.75mm White (100m)



General Information

Brand	Cable & Wire Generic
Product Type	Flexible Cable
Type	Flexible
Unit Weight	5.6 kg
CE Approved	N
Number of Cores	2
Core Identification	Coloured
Earth Core	N
Conductor Material	Copper
Conductor Construction	Plain Annealed Flexible
Insulation Type	PVC
Armoured	N
FIRE RESISTANT	N
Minimum Bending Radius	34.2-43.2
Flexibility class	5
Magnetic armour	N
Earthed Metallic Covering	N
Core Colours	Blue Brown
Outer Sheath Material	PVC
Outer Sheath Colour	White
Drum Length	100 Metres
Cable Diameter	5.7-7.2 mm
Conductor Size	0.75 mm ²
Stranding Size	24/0.2 mm
Minimum Temperature Rating	-15 Degrees C
Maximum Temperature Rating	70 Degrees C
Voltage Rating	300/500 V



Datasheet

SKU: 3182Y075HW

Conforming Standard

BS EN 50525-2-11:2011
Clause 4.2 Table B.2 BS
EN 60228 BS EN 50363-3
BS EN 50363-4-1

LU1085 Approved?

N

www.erfelectrical.co.uk
customerservices@erfelectrical.co.uk
01623 638747

