



Cable & Accessories | House Wiring Cables

Cable, 3 Core Circular Flex PVC/PVC, 100m Reel (Price Per Mtr)

3183Y 3C Flex PVC 2.5mm Blk (100m)



General Information

Brand	Cable & Wire Generic
Product Type	Flexible Cable
CE Approved	N
Qualifier	Electrical
Unit Weight	15 kg
Voltage Rating	300/500 V
Number of Cores	3
Core Identification	Coloured
Earth Core	Y
Conductor Material	Copper
Conductor Construction	Plain Annealed Flexible
Insulation Type	PVC
Armoured	N
Fire Resistant	N
Magnetic armour	N
Earthed Metallic Covering	N
Core Colours	Green/Yellow Blue Brown
Outer Sheath Colour	Grey
Cable Diameter	9.2-11.4 mm
Stranding Size	50/0.25 mm
Outer Sheath Material	PVC
Drum Length	100 Metres
Note	100m Reel
Minimum Bending Radius	55.2-68.4
Flexibility class	5
Conductor Size	6 mm ²
Minimum Temperature Rating	-15 Degrees C



Datasheet

SKU: 3183Y25HB

Maximum Temperature Rating	70 Degrees C
Conforming Standard	BS EN 50525-2-11:2011 Clause 4.2 Table B.2 BS EN 60228 BS EN 50363-3 BS EN 50363-4-1
LU1085 Approved?	N

