SKU: **6943XH15**

Datasheet

Cable & Accessories | SWA, SY, CY

Cable 6943XLH 3 Core SWA PVC 1.5mm Blk

Cable 6943XLH 3 Core SWA PVC 1.5mm Black



General Information

Brand	Cable & Wire Generic
Product Type	Armoured Cable SWA
Type	Armoured
Unit Weight	260 kg
CE Approved	N
Number of Cores	3
Core Identification	Coloured
Earth Core	N
Conductor Material	Copper
Conductor Construction	Stranded Plain Annealed
Insulation Type	XLPE Thermosetting
Armoured	Y
FIRE RESISTANT	N
Minimum Bending Radius	95.2
Flexibility class	2
Magnetic armour	N
Earthed Metallic Covering	N
Core Colours	Brown Black Grey
Outer Sheath Material	PVC
Outer Sheath Colour	Black
Drum Length	1000 Metres
Cable Diameter	11.9 mm
Conductor Size	1.5 mm2
Stranding Size	7/0.53 mm
Minimum Temperature Rating	-15 Degrees C
Maximum Temperature Rating	90 Degrees C
Voltage Rating	600/1000 V
Conforming Standard	BS 5467 Table 8 BS EN 60228 BS 7655-1.3 BS 7655-4.2
LU1085 Approved?	N
Bedding Material	PVC
Armour Material	Galvanised Steel Wire

www.erfelectrical.co.uk
customerservices@erfelectrical.co.uk
01623 638747

Gland Size Required	20S

www.erfelectrical.co.uk
customerservices@erfelectrical.co.uk
01623 638747

Company Registration Number: 00911692. This document is uncontrolled if printed, all information is subject to change. Generated on 29/03/24