



Cable & Accessories | SWA, SY, CY

Cable 6943XLH 3 Core SWA PVC 16mm Blk

Cable 6943XLH 3 Core SWA
PVC 16mm Black



General Information

Brand	Cable & Wire Generic
Product Type	Armoured Cable SWA
Type	Armoured
Unit Weight	1075 kg
CE Approved	N
Number of Cores	3
Core Identification	Coloured
Earth Core	N
Conductor Material	Copper
Conductor Construction	Stranded Plain Annealed
Insulation Type	XLPE Thermosetting
Armoured	Y
FIRE RESISTANT	N
Minimum Bending Radius	163.2
Flexibility class	2
Magnetic armour	N
Earthed Metallic Covering	N
Core Colours	Brown Black Grey
Outer Sheath Material	PVC
Outer Sheath Colour	Black
Drum Length	1000 Metres
Cable Diameter	20.4 mm
Conductor Size	16 mm ²
Stranding Size	7/1.70 mm
Minimum Temperature Rating	-15 Degrees C
Maximum Temperature Rating	90 Degrees C
Voltage Rating	600/1000 V
Conforming Standard	BS 5467 Table 8 BS EN 60228 BS 7655-1.3 BS 7655-4.2
LU1085 Approved?	N
Bedding Material	PVC

www.erfelectrical.co.uk
customerservices@erfelectrical.co.uk
01623 638747



Gland Size Required

25