



Cable & Accessories | SWA, SY, CY

Cable 6944XLH 4 Core SWA PVC 16mm Blk

Cable 6944XLH 4 Core SWA
PVC 16mm Black



General Information

Brand	Cable & Wire Generic
Product Type	Armoured Cable SWA
Type	Armoured
Unit Weight	1400 kg
CE Approved	N
Number of Cores	4
Core Identification	Coloured
Earth Core	N
Conductor Material	Copper
Conductor Construction	Stranded Plain Annealed
Insulation Type	XLPE Thermosetting
Armoured	Y
FIRE RESISTANT	N
Minimum Bending Radius	182.4
Flexibility class	2
Magnetic armour	N
Earthed Metallic Covering	N
Core Colours	Blue Brown Black Grey
Outer Sheath Material	PVC
Outer Sheath Colour	Black
Drum Length	1000 Metres
Cable Diameter	22.8 mm
Conductor Size	16 mm ²
Stranding Size	7/1.70 mm
Minimum Temperature Rating	-15 Degrees C
Maximum Temperature Rating	90 Degrees C
Voltage Rating	600/1000 V
Conforming Standard	BS 5467 Table 10 BS EN 60228 BS 7655-1.3 BS 7655-4.2
LU1085 Approved?	N
Bedding Material	PVC

www.erfelectrical.co.uk
customerservices@erfelectrical.co.uk
 01623 638747

Armour Material

Galvanised Steel Wire



Gland Size Required

25