



Lighting, Lamps & Bulbs | LED Flood Lights

Toughflood Commercial

JCC JC050007 Floodlight LED
4000K 150W



General Information

| | |
|------------------------------------|---|
| Brand | JCC Lighting Products |
| Product Type | LED Flood Light |
| CE Approved | Y |
| Standards | ISO9001-2015 ISO14001-2015 BS EN 60598-2015 2-1 2-5 |
| Length | 313 mm |
| Width | 360 mm |
| Depth | 38 mm |
| Cover Material | Polycarbonate |
| Height | 313 mm |
| Ingress Protection | IP65 |
| Operating Temperature Range | -20 40 Degrees C |
| Warranty | 3 Years |
| Unit Weight | 2.45 kg |
| Voltage | 220-240 V |
| Face Shape | Rectangular |
| Mounting Position | Wall |
| Mounting Type | Surface |
| Adjustability | Fixed |
| Fire Rated | N |
| Dimmable | N |
| Corrosion Resistant | Y |
| Vandal Resistant | N |
| Microwave Sensor Included | N |
| Photocell Included | N |
| PIR Included | N |
| Cover Included | Y |



Datasheet

SKU: JC050007

| | |
|---------------------------------|-------------|
| Ballast/Starter Included | N |
| LED Driver Included? | Y |
| Lamp(s) Included? | Y |
| Emergency | N |
| Self-Contained | N |
| Housing Material | Aluminium |
| Housing Colour | Black |
| Bezel/Trim Colour | Black |
| Lamp Type | LED Fixed |
| Cover Type | Diffuser |
| Wattage | 150 W |
| Cover Colour | Opal |
| Beam Angle | 110 Degrees |
| Colour Temperature | 4000 K |
| Light Output | 16300 Lm |
| Luminous Efficiency | 109 Lm/W |
| Energy Efficiency Class | E |
| Colour Rendering Index | 50-79 |
| Average Lifespan | 54000 Hours |
| UKCA Approved | Y |
| Impact Strength | IK08 |

