



Lighting, Lamps & Bulbs | LED Bulkheads

RadiaLED® Rapid

JCC JC070075 RadiaLED B/Hd
12W



General Information

| | |
|------------------------------------|--|
| Brand | JCC Lighting Products |
| Product Type | LED Bulkhead |
| CE Approved | Y |
| Standards | ISO9001-2015 ISO14001-2015 BS EN 60598-2-1 |
| Cover Material | Polycarbonate |
| Height | 98.3 mm |
| Ingress Protection | IP65 |
| Operating Temperature Range | 0 45 Degrees C |
| Warranty | 5 Years |
| Unit Weight | 1.2 kg |
| Voltage | 220-240 V |
| Face Shape | Circular |
| Mounting Position | Ceiling/Wall |
| Mounting Type | Surface |
| Adjustability | Fixed |
| Fire Rated | N |
| Dimmable | N |
| Corrosion Resistant | N |
| Vandal Resistant | N |
| Microwave Sensor Included | N |
| Photocell Included | N |
| PIR Included | N |
| Cover Included | Y |
| Ballast/Starter Included | N |
| LED Driver Included? | Y |
| Lamp(s) Included? | Y |
| Emergency | N |



Datasheet

SKU: JC070075

| | |
|--------------------------------|---------------|
| Self-Contained | N |
| Housing Material | Polycarbonate |
| Housing Colour | White |
| Bezel/Trim Colour | White |
| Overall Diameter | 340 mm |
| Lamp Type | LED Fixed |
| Cover Type | Diffuser |
| Wattage | 12 W |
| Cover Colour | Opal |
| Beam Angle | 116 Degrees |
| Colour Temperature | 4000 K |
| Light Output | 1250 Lm |
| Luminous Efficiency | 100 Lm/W |
| Energy Efficiency Class | F |
| Colour Rendering Index | 80-89 |
| Average Lifespan | 60000 Hours |
| UKCA Approved | Y |
| Impact Strength | IK10 |

