



Lighting, Lamps & Bulbs | LED Flood Lights

Floodlight, LED 4000K IP65

JCC JC091005 LED Fld/Lgt
30W Blk



General Information

| | |
|--------------------------|-----------------------|
| Brand | JCC Lighting Products |
| Product Type | LED Floodlight |
| Lamp Type | LED Fixed |
| Face Shape | Rectangular |
| Mounting Position | Wall |
| Product | Luminaire |
| Housing Material | Aluminium |
| Housing colour | Black |
| Bezel/Trim Colour | Black |
| Cover Colour | Opal |
| Cover Material | Glass |
| Mounting Type | Surface |
| Adjustability | Adjustable |
| Fire Rated | N |
| Dimmable | N |
| Corrosion Resistant | N |
| Vandal Resistant | N |
| PIR Included | N |
| Cover Type | Diffuser |
| Ballast/Starter Included | N |
| LED Driver Included? | Y |
| Lamp(s) Included? | Y |
| Emergency | N |
| Self-Contained | N |
| Wattage | 30 W |
| Ingress Protection | IP65 |
| Cover Included | Y |
| Photocell Included | N |



Datasheet

SKU: JC091005

| | |
|------------------------------------|---|
| Microwave Sensor Included | N |
| Width | 173.6 mm |
| Height | 139 mm |
| Depth | 173.6 mm |
| Length | 139 mm |
| Average Lifespan | 54000 Hours |
| Beam Angle | 100 Degrees |
| Colour Temperature | 4000 K |
| Colour Rendering Index | 80-89 |
| Light Output | 3200 Lm |
| Luminous Efficiency | 107 Lm/W |
| Operating Temperature Range | -10 30 Degrees C |
| Voltage | 220-240 V |
| Energy Efficiency Class | E |
| Standards | ISO9001-2015 ISO14001-2015 BS EN 60598-2015 2-1 2-5 |
| Unit Weight | 0.497 kg |
| Warranty | 2 Years |
| CE Approved | Y |

