



## Wiring Accessories | White Moulded

### MK K1090WHI Frontplate 1G FO 20A

Frontplate, 1 Gang Flex Outlet  
Unfused



#### General Information

Brand	MK Electric
Product Type	Flex Outlet
Lamp Base	Flush
Wattage	BS EN 60670-22:2006
Colour Temperature	86 mm
Light Output	12.5 mm
Colour Rendering Index	86 mm
Voltage	IP2XD
Type	20 A
Lamp Shape	250 V
Type of glass/cover	Double Pole (2P)
Integral Ballast	1 Gang
Diameter	White
Energy Efficiency Class	Unswitched
Warranty	N
Unit Weight	N
Extra Information	N
Material	Y
Qualifier	N
Voltage (max)	N
Insulated	N
Terminal Material	N
Cable Size Range	N
Hole/Stud Size	N
Current Rating (max)	N
Insulation Colour	N
Insulation Material	N
Thread Type	N
Finish	N
Nominal Width	N
Nominal Width B	Moulded Urea
Fixings Included	60.3 mm

[www.erfelectrical.co.uk](http://www.erfelectrical.co.uk)  
[customerservices@erfelectrical.co.uk](mailto:customerservices@erfelectrical.co.uk)  
01623 638747





## Datasheet

SKU: MKK1090WHI

Rated Voltage

Rated Current

CE Approved

Number of Cores

Core Identification

Earth Core

Conductor Material

Conductor Construction

Insulation Type

Armoured

Fire Resistant

Minimum Bending Radius

Flexibility class

Magnetic armour

Earthed Metallic Covering

Core Colours

Outer Sheath Material

Outer Sheath Colour

Drum Length

Cable Diameter

Conductor Size

Stranding Size

Minimum Temperature Rating

Maximum Temperature Rating

Voltage Rating

Conforming Standard

LU1085 Approved?

Wiring Method

c/w Battery Backup

Backup Battery Type

Shape

Set

Angle

External Pipe Diameter

Use

Number of Pins

Pin Shape

[www.erfelectrical.co.uk](http://www.erfelectrical.co.uk)  
[customerservices@erfelectrical.co.uk](mailto:customerservices@erfelectrical.co.uk)  
01623 638747





## Datasheet

SKU: MKK1090WHI

Bedding Material

Armour Material

Gland Size Required

Number of Poles

Switch Position

Motor Power

Overall Length

Overall Width

Overall Depth

Frequency

Maximum Sound Pressure  
Level

Equivalent Wattage

Ballast/Starter Included

LED Driver Included?

Housing Colour

Rocker Colour

Indicator Colour

Shank Type

Ways

Legend

Corner Shape

Number of Gangs

Entry Method

Number of Entries

Fused Fitted

Switched

Earth Included

Knockouts Included?

Number of Knockouts

Knockout Shape

Multi Compartment

Trip Type

Short Circuit Rating

Number of Ways

c/w Indicator

Fitting Hole Centres

[www.erfelectrical.co.uk](http://www.erfelectrical.co.uk)  
[customerservices@erfelectrical.co.uk](mailto:customerservices@erfelectrical.co.uk)  
01623 638747



Sensitivity

Cable Capacity