



Wiring Accessories | White Moulded

MK K422WHI Socket 1Gang Tel Master

Socket, 1 Gang Telephone
Master



General Information

Brand	MK Electric
Product Type	Telephone Outlet
Lamp Type	Flush
Wattage	BS 6312 BS 5733 OFTEL
Colour Temperature	86 mm
Voltage	86 mm
Luminous Efficiency	IP2XD
Type of glass/cover	1 Gang
Ingress Protection	White
Colour	White
Integral LED Driver	Unswitched
Diameter	Moulded Urea
Average Lifespan	60.3 mm
Beam Angle	25 mm
Material	
Qualifier	
Voltage (max)	
Insulated	
Terminal Material	
Cable Size Range	
Hole/Stud Size	
Current Rating (max)	
Insulation Colour	
Insulation Material	
Thread Type	
Finish	
Nominal Width	
Nominal Width B	
Fixings Included	
Rated Voltage	
Rated Current	

www.erfelectrical.co.uk
customerservices@erfelectrical.co.uk
01623 638747





Datasheet

SKU: MKK422WHI

Core Identification

Earth Core

Conductor Material

Conductor Construction

Insulation Type

Armoured

Fire Resistant

Minimum Bending Radius

Flexibility class

Magnetic armour

Earthed Metallic Covering

Core Colours

Outer Sheath Material

Outer Sheath Colour

Drum Length

Cable Diameter

Conductor Size

Stranding Size

Minimum Temperature Rating

Maximum Temperature Rating

Voltage Rating

Conforming Standard

LU1085 Approved?

Wiring Method

c/w Battery Backup

Backup Battery Type

Shape

Set

Angle

External Pipe Diameter

Use

Pole Configuration

Number of Pins

Pin Shape

Current Rating

Bedding Material

Armour Material

www.erfelectrical.co.uk
customerservices@erfelectrical.co.uk
01623 638747





Datasheet

SKU: MKK422WHI

Gland Size Required

Number of Poles

Switch Position

Motor Power

Overall Length

Overall Width

Overall Depth

Frequency

Maximum Sound Pressure
Level

Equivalent Wattage

Ballast/Starter Included

LED Driver Included?

Housing Colour

Indicator Colour

www.erfelectrical.co.uk
customerservices@erfelectrical.co.uk
01623 638747

