



Wiring Accessories | White Moulded

MK K4875WHI Switch 1 Gang Intermed 10A

Plate Switch, 1 Gang Intermediate



General Information

Brand	MK Electric
Product Type	Plateswitch
Lamp Base	Flush
Overall Diameter	BS EN 60669-1
Light Output	86 mm
Voltage	86 mm
Luminous Efficiency	IP2XD
Width	10 A
Depth	250 V
Type	Single Pole (1P)
Lamp Shape	1 Gang
Type of glass/cover	Intermediate
Dimmable	White
Ingress Protection	White
Colour	Switched
Integral Ballast	Moulded Urea
Integral LED Driver	60.3 mm
Diameter	16 mm
Average Lifespan	
Beam Angle	
Energy Efficiency Class	
Warranty	
Unit Weight	
Extra Information	
Material	
Qualifier	
Voltage (max)	
Insulated	
Terminal Material	
Cable Size Range	
Hole/Stud Size	
Current Rating (max)	

www.erfelectrical.co.uk
customerservices@erfelectrical.co.uk
01623 638747





Datasheet

SKU: MKK4875WHI

Insulation Material

Thread Type

Finish

Nominal Width

Nominal Width B

Fixings Included

Rated Voltage

Rated Current

CE Approved

Number of Cores

Core Identification

Earth Core

Conductor Material

Conductor Construction

Insulation Type

Armoured

Fire Resistant

Minimum Bending Radius

Flexibility class

Magnetic armour

Earthed Metallic Covering

Core Colours

Outer Sheath Material

Outer Sheath Colour

Drum Length

Cable Diameter

Conductor Size

Stranding Size

Minimum Temperature Rating

Maximum Temperature Rating

Voltage Rating

Conforming Standard

LU1085 Approved?

Wiring Method

c/w Battery Backup

Backup Battery Type

www.erfelectrical.co.uk
customerservices@erfelectrical.co.uk
01623 638747





Datasheet

Set

Angle

External Pipe Diameter

Use

Number of Pins

Pin Shape

Bedding Material

Armour Material

Gland Size Required

Number of Poles

Switch Position

Motor Power

Overall Length

Overall Width

Overall Depth

Frequency

Maximum Sound Pressure
Level

Equivalent Wattage

Ballast/Starter Included

LED Driver Included?

Housing Colour

Indicator Colour

Legend

Insert Colour

